

CIIROL CARRIER CUT 2**Description:**

CIIROL CARRIER CUT 2 is chlorine and heavy metal free neat cutting oil based on advanced biodegradable ester technology. It is especially formulated with a unique combination of sulphur and phosphorus based anti-wear additives to optimise machining performance, enhance surface finish and lower the overall operating costs.

Applications:

CIIROL CARRIER CUT 2 is designed for high speed, creep feed and gear grinding of ferrous and non ferrous metals. It can also be used for drilling and general machining applications, as well as for hard metal and tool grinding.

Specifications:

This is a propriety formulation of SRN LUBRICANTS Pvt. Ltd..

Benefits:

- Excellent flushing and lubrication properties extend grinding wheel life and enable high surface finish and dimensional accuracy.
- Low viscosity and excellent wetting properties reduce drag out and results in lower product usage.
- Good filtering characteristics and high oxidation stability help increase product lifetime
- Our chlorine, mineral oil and heavy metal free formulation, based on advanced biodegradable ester technology improves the environmental profile and can help reduce disposal costs.
- Good viscosity temperature characteristics for wide operating temperatures.
- Outstanding anti-wear, anti-corrosion and antirust characteristics
- High flashpoint, low odour, light colour and low mist qualities improve the work environment
- Multi-metal machining using our superior additive technology provides opportunity for product consolidation.

GURUGRAM PLANT : Plot No.24, Village Darbaripur

Kewat No.86/75, Khata no.90 mustil No.8 Kila No.-23/2

Tehsil Badshahpur, Dist. Gurugram-122101

Mob. 9717972626, 9727179657

Website: www.ciirol.co.in

Sanjay.ciirol@gmail.com



SRN LUBRICANTS PRIVATE LIMITED
PRODUCT DATA SHEET



TYPICAL PROPERTIES
CIIFROL CARRIER CUT 2

Name	Method	Units	CIIFROL CARRIER CUT 2
Appearance	Visual	-	Clear Colourless Liquid
Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	3
Density at 29.5°C	DIN 51757, ASTM D 1298	kg/m ³	0.800
Flash Point, COC	DIN 51376	°C	100
Copper Corrosion, 3 hr at 100°C	DIN 51811, ASTM D 130	-	1b

The above given values are typical results; however the guaranteed specifications values are different and often lower than the typical values. For the guaranteed specifications, please discuss with SRN LUBRICANTS PVT. LTD. representative or visit our website www.ciifrol.co.in

GURUGRAM PLANT : Plot No.24,Village Darbaripur
Kewat No.86/75,Khata no.90 mustil No.8Kila No.-23/2
Tehsil Badshahpur,Dist.Gurugram-122101
Mob. 9717972626, 9727179657
Website:www.ciifrol.co.in,
Sanjay.ciifrol@gmail.com